




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup> :</b>  <b>F01N 1/06</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 93/09334</b>  <b>(43) International Publication Date:</b> <b>13 May 1993 (13.05.93)</b>
<b>(21) International Application Number:</b> <b>PCT/US91/07831</b> <b>(22) International Filing Date:</b> <b>30 October 1991 (30.10.91)</b>  <b>(71) Applicant (for all designated States except US):</b> <b>NOISE CANCELLATION TECHNOLOGIES, INC. [US/US];</b> <b>1015 West Nursery Road, Suite 101, Linthicum, MD 21090 (US).</b>  <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only) :</b> <b>LANGLEY, Andrew, J. [GB/GB]; 28 Canons Field, Welwyn, Hertfordshire AL6 0QD (GB).</b>  <b>(74) Agent:</b> <b>HINEY, James, W.; Noise Cancellation Technologies, Inc., 1015 West Nursery Road, Suite 101, Linthicum, MD 21090 (US).</b>		<b>(81) Designated States:</b> <b>CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, NL, SE).</b>  <b>Published</b> <i>With international search report.</i>

**(54) Title:** **ACTIVELY SOUND REDUCED MUFFLER HAVING A VENTURI EFFECT CONFIGURATION**

**(57) Abstract**

In an actively sound dampened muffler, the improvement of a venturi effect area (22) producing means adjacent an aperture (23) in said muffler near which is mounted a loudspeaker (25) in an enclosure (24), the venturi effect area (22) preventing hot exhaust gases from impinging on the loudspeaker (25).

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LI	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

**Actively Sound Reduced Muffler having a Venturi Effect Configuration**

In the design of active noise controlled mufflers a common problem is the resulting lengthy extension which protrudes beyond the main enclosure to the end of the vehicle resulting in an unattractive "snout". Beyond the physical undesirability of this extension there is a more serious problem created and that is the large acoustic air mass that resides in the snout. As this air mass is extremely difficult to move to and fro at high frequencies the result is a small amount of anti-sound being generated.

To overcome this problem it is proposed to keep the extension or snout short which reduces the moving mass. The solution has typically resulted in a configuration that has a very short link between the loudspeaker and the pipe and wherein the loudspeaker is typically placed far from the engine for the benefit of reduced sound pressure and temperature. The controller can then cancel the exhaust noise provided only one acoustic mode can propagate in the exhaust pipe over the control bandwidth. The loudspeaker enclosure volume may be reduced somewhat and the diameter of the tail-pipe need not be larger than normal. The problems with this solution were that the loudspeaker is subjected to high temperatures as well as the corrosive effects of exhaust gases.

To solve these residual problems the instant invention manipulates the mean flow of the exhaust gases to cool the loudspeaker enclosure. Either a full or partial venturi is used to generate an area that is below atmospheric pressure. A bleed pipe allows ambient air to flow into this area thereby counteracting the flow of exhaust gases into the speaker area. A filter can be provided in the bleed pipe to reduce the radiated noise. Additionally a heat shield can be employed to protect the loudspeaker from the exhaust pipe or, instead, a reflective coated layer that conducts sound. To prevent a sudden reversal of the cooling air the configuration is designed to allow the cooling flow to maintain the exhaust gas concentration in the front cavity at a reasonable level. A diffuser section can

be used to accomplish this as well as a contracted section followed immediately by an expansion section. Cooling can also be accomplished by using the cooling fluid of the vehicle or by using separate fans. Both would entail additional expenditures and add a degree of complexity to the configuration.

Therefore, it is an object of this invention to provide an improved muffler that eliminates the long loudspeaker enclosure.

Another object of this invention is to provide an actively controlled noiseless muffler having a short connection between the exhaust pipe and the loudspeaker enclosure.

A further object of this invention is to an active noise cancellation system for an exhaust system wherein the diameter/size of the exhaust pipe can be of standard size.

A still further object of this invention is to provide an actively controlled muffler configuration that prevents ingestion of exhaust gases into the loudspeaker enclosure.

Yet another object of this invention is the provision of a venturi means in an active noise cancellation exhaust system to create a differential pressure adjacent the speaker enclosure.

These and other objects of this invention not specifically enumerated herein will become apparent as reference is made to the following detailed discussion and drawings in which

Fig 1 is a diagrammatic view of a standard active noise cancellation muffler, and

Fig 2 is a diagrammatic view of an improved configuration of an improved active noise cancellation muffler system and

Fig 3 is a diagrammatic view of an in-pipe or venturi configuration in an improved active noise cancellation muffler, and

Fig 4 is a diagrammatic view of a venturi nozzle configuration in an active noise cancellation muffler to reduce radiation heating , and

Fig 5 is another diagrammatic view of an in-pipe or venturi configuration in an improved active noise cancellation muffler showing a separate heat shield, and

Fig 6 is a diagrammatic view of a partial venturi nozzle configuration in an active noise cancellation muffler.

Referring to the figures, Fig 1 shows a state-of-the-art active noise cancellation muffler having an exhaust pipe 1, a speaker enclosure 2 containing a loudspeaker 3 and having an extension which is co-axial and larger than pipe 1 and which also extends back beyond fender 5 and terminates in the same plane as pipe 1.

Demands on the performance of the muffler suggest that the loudspeakers must function up to 500Hz and this causes considerable problems in the design of the loudspeaker units for the following reasons:

- (a) The current design of the active muffler requires the loudspeaker units to be positioned in front of the rear fender, and yet the exit from the loudspeaker enclosure must be at the end of the muffler pipe which is behind the fender.
- (b) Inevitably, this leads to a "snout" on the enclosure that is several inches long, and the acoustic mass of the air in the snout is considerable.
- (c) At high frequencies it is difficult to move the slug of air in the snout backwards and forwards sufficiently to generate much anti-sound. This requires a very small volume between the loudspeaker and the snout, and results in a very large magnet assembly for the loudspeaker unit.

In order to avoid the large moving mass of the snout, it is essential to keep the snout very short indeed, and this precludes the use of the current design.

Fig 2 shows an improved system wherein the noise is cancelled directly in the muffler pipe. Exhaust pipe 11 is directly open to enclosure 12 containing loudspeaker 13. There is no long extension or snout and the advantages of this configuration are

- (a) the link between the loudspeaker and the pipe can be very short, therefore reducing the moving mass;

- (b) The active system can be placed at any convenient location in the muffler pipe (although far from the engine has the benefits of reduced sound pressure and temperature);
- (c) provided only one acoustic mode can propagate in the exhaust pipe over the control bandwidth, the controller can in principle "cancel" the exhaust noise perfectly; this is not the case with the state of the art configuration because the source and anti-source are not quite coincident;
- (d) the diameter of the tail-pipe on the muffler need be little, if any, larger than it would be on a passive system;
- (e) overall loudspeaker enclosure volume is reduced somewhat.

The main disadvantages of this improved configuration, however are:

- (a) the high temperature that the loudspeaker unit might be subject to;
- (b) ingestion of exhaust gases into the front cavity or the loudspeaker enclosure and consequent corrosion.

In order to circumvent these problems, the present invention manipulates the mean flow of the exhaust gases to force a clean, cooling airflow through the front (and/or back) cavities of the loudspeaker enclosure. One configuration is shown in figure 3.

An exhaust pipe 21 has a reduced section as at 22 so as to produce a low pressure region at opening 23 into enclosure 24. Loudspeaker 25 is mounted in enclosure 24 so as to cancel, by counter-sound, noise emanating at the exit 28.

The smooth contraction/expansion (a "venturi") 22 is used to generate locally in the pipe a region that is below atmospheric pressure. A bleed pipe 26 in the front cavity of the loudspeaker enclosure 24 permits air from outside to flow towards the low pressure region, thereby reducing ingestion of exhaust gases into the loudspeaker enclosure, and also providing cooling.

By keeping the entrance 27 to the bleed pipe a little away from the exhaust exit 28, a cleaner flow will result, and help to reduce corrosion. On the other hand, some

sound will escape from the bleed pipe, and it is advantageous to position the entrance of the bleed pipe close to the residual error microphone 29 so that the control system will "cancel" the combined sound of the exhaust and bleed pipe noises. If pipe 26 is quite long, and not too large in diameter, radiation will not be very strong and will be very frequency selective. The addition of a filter in the bleed pipe could also help to reduce the radiated noise. When radiation from the bleed pipe is not a problem, its entrance can be placed wherever is convenient.

Bleed-pipe routing should avoid water traps ("sumps"), and it may be possible for the bleed pipe to drain the loudspeaker enclosure in the event of flooding.

To avoid having the loudspeaker unit(s) face directly into the hole in the muffler pipe since radiation of heat from the hot gasses could then directly heat the loudspeaker diaphragms (this may not be a serious problem as the emissivity of the gas is likely to be much lower than that of the pipe), the hole 42 in the muffler pipe 41 is arranged so that the loudspeaker is shielded by the muffler pipe itself. See figure 4. A bleed pipe 45 conducts a cooling flow into speaker enclosure 44.

As shown in Fig 5 a separate heat shield 52 can be used in conjunction with exhaust pipe 51 with its opening 53 across from loudspeaker 54 in speaker enclosure 55. A cooling flow is brought in through cooling bleed pipe 56.

The heat shield can be a reflective coated substratum that is acoustically transparent (e.g. a coated "foam"; overlapping, separated grids etc.) and span most or all of the width of the front cavity, or it can be a solid shield just large enough to "shadow" the diaphragm from the hot components without introducing significant acoustic blockage. It can be adequate just to have a reflective coating on heat-sensitive parts such as the diaphragm.

The crucial aspects of this design are:

- (a) generating the cooling flow with the minimum backpressure for the exhaust flow; and

(b) the detailed fluid mechanics of the flow through the section in order to reduce turbulence, ingestion of gases into the loudspeaker enclosure (despite the cooling flow), flow-excited instabilities and flow noise.

Although on average the cooling flow will be flowing into the muffler pipe, the strong oscillatory component in the muffler flow and the anti-sound may cause the flow to reverse instantaneously and ingest exhaust gases into the loudspeaker enclosure. This is not a problem provided that on average the cooling flow keeps the exhaust gas concentration in the front cavity at a reasonable level.

The classical venturi arrangement of a smooth contraction followed by a diffuser section is not the only way of producing a low pressure region in the muffler flow (although it is a good one), for example a contraction followed by an abrupt expansion will also work, but with potentially higher backpressure penalties. One example of an alternative to the full venturi is sketched in figure 6. The principle of the idea is that the mean flow of the exhaust gasses is manipulated in such a way that an auxiliary cooling flow can be generated.

An exhaust pipe 61 is shown to have a partial venturi effect produced by split opening 62 which opens the pipe to speaker enclosure 63 containing loudspeaker 64 and bleed pipe 65.

Forced cooling of the loudspeakers by e.g. fans can obviously be done, but this would increase the complication and cost of the system. It is also possible to use the car's forward motion to drive a cooling flow over the loudspeakers, but this would not work with the car stationary. Cooling with fluid (e.g. by tapping into the engine-cooling circuit) will also work, again at the cost of complexity, but it might be difficult to get sufficient cooling on moving parts such as the diaphragms.

Having described several aspects of the invention it is anticipated that other variations will occur to those of ordinary skill in the art without departing from the scope of the appended claims.



What is claimed is as follows:

1. An actively noise cancelled muffler system comprising  
an exhaust pipe means, with aperture means, a loudspeaker enclosure means  
mounted adjacent said exhaust pipe means, and over said aperture means said  
enclosure means containing at least one loudspeaker means adapted to produce  
opposite sound from that emanating from said exhaust pipe through said aperture  
means.
2. A system as in claim 1 and including  
a venturi effect area producing means in said exhaust pipe means adjacent said  
aperture means, and  
a conduct means for allowing ambient air to flow to said venturi effect area to  
thereby prevent or inhibit any exhaust gases from coming into contact with said  
loudspeaker means.
3. A system as in claim 2 wherein said venturi effect area producing means is a  
reduced cross-sectional area of said exhaust pipe means.
4. A system as in claim 2 wherein said conduit means a bleed pipe, one end of  
which is adjacent said venturi effect area and the other end is spaced from the end  
of said exhaust pipe means.
5. A system as in claim 1 wherein said enclosure means surrounds part of said  
exhaust pipe means.
6. A system as in claim 5 wherein said aperture means on said exhaust pipe means is  
located on the side thereof opposite from said loudspeaker means.
7. A system as in claim 2 including a depressed cross sectional area of said exhaust  
pipe means, area containing said aperture means.
8. A system as in claim 7 wherein said depressed cross sectional area of said exhaust  
pipe means is adapted to produce a low pressure region and

an acoustically transparent heat shield means is located between said low pressure region and said loudspeaker means.

9. A system as in claim 8 and including a conduit means adapted to deliver ambient cooling air to said low pressure region.
10. A system as in claim 9 wherein said conduit means is a bleed pipe.

FIG.1





FIG.2






FIG. 3




FIG. 5




FIG. 4




FIG. 6

# INTERNATIONAL SEARCH REPORT

International Application No. PCT/US91/07831

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (If several classification symbols apply, indicate all) <sup>6</sup> According to International Patent Classification (IPC) or to both National Classification and IPC IPC (5): F01N 1/06 U.S.C.I.: 181/206											
<b>II. FIELDS SEARCHED</b> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Minimum Documentation Searched <sup>7</sup></div> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 25%; border-bottom: 1px solid black;">Classification System</th> <th style="border-bottom: 1px solid black;">Classification Symbols</th> </tr> <tr> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">U.S.</td> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">181/206 381/71</td> </tr> </table> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; margin: 5px 0;">Documentation Searched other than Minimum Documentation to the extent that such Documents are included in the Fields Searched <sup>8</sup></div>			Classification System	Classification Symbols	U.S.	181/206 381/71					
Classification System	Classification Symbols										
U.S.	181/206 381/71										
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT <sup>9</sup></b> <table style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; border-bottom: 1px solid black;">Category <sup>10</sup></th> <th style="width: 60%; border-bottom: 1px solid black;">Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup></th> <th style="width: 30%; border-bottom: 1px solid black;">Relevant to Claim No. <sup>13</sup></th> </tr> <tr> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">X, E Y, E</td> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">US, A, 5,088,575 (ERIKSSON) 18 February 1992 See the entire document.</td> <td style="border: 1px solid black; vertical-align: top; padding: 5px; text-align: center;">1-7 8-10</td> </tr> <tr> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">X Y</td> <td style="border: 1px solid black; vertical-align: top; padding: 5px;">US, A, 5,044,464 (BREMIGAN) 03 September 1991 See the entire document.</td> <td style="border: 1px solid black; vertical-align: top; padding: 5px; text-align: center;">1,5,6 2-4, 7-10</td> </tr> </table>			Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>	X, E Y, E	US, A, 5,088,575 (ERIKSSON) 18 February 1992 See the entire document.	1-7 8-10	X Y	US, A, 5,044,464 (BREMIGAN) 03 September 1991 See the entire document.	1,5,6 2-4, 7-10
Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>									
X, E Y, E	US, A, 5,088,575 (ERIKSSON) 18 February 1992 See the entire document.	1-7 8-10									
X Y	US, A, 5,044,464 (BREMIGAN) 03 September 1991 See the entire document.	1,5,6 2-4, 7-10									
<div style="display: flex; justify-content: space-between;"> <div style="width: 48%;"> <p><sup>14</sup> Special categories of cited documents: <sup>15</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 48%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"A" document member of the same patent family</p> </div> </div>											
<b>IV. CERTIFICATION</b> <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of the Actual Completion of the International Search</td> <td style="width: 50%; border-bottom: 1px solid black; padding: 5px;">Date of Mailing of this International Search Report</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">01 June 1992</td> <td style="border-bottom: 1px solid black; padding: 5px; text-align: center;">22 JUN 1992</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">International Searching Authority</td> <td style="border-bottom: 1px solid black; padding: 5px;">Signature of Authorized Officer</td> </tr> <tr> <td style="border-bottom: 1px solid black; padding: 5px;">ISA/US</td> <td style="border-bottom: 1px solid black; padding: 5px;">Eddie C. Lee </td> </tr> </table>			Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	01 June 1992	22 JUN 1992	International Searching Authority	Signature of Authorized Officer	ISA/US	Eddie C. Lee	
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report										
01 June 1992	22 JUN 1992										
International Searching Authority	Signature of Authorized Officer										
ISA/US	Eddie C. Lee										